

TENSIONER PUMPS — AIR

power pack.

**STANDARD POWER PACK
HPUTP150001K****Typical uses: Topside bolt tensioners,
hydraulic nuts**

- 1500 bar (21,750 psi) max working pressure (restricted)
- Calibrated 150mm (6") Pressure gauge
- Flow Rate up to 0.72 litres/min (44 cu.in/min)
- Dual oil outlets with quick-connect no spill couplings
- Pneumatic Filter/Regulator/Lubricator
- Air Consumption 800 litres/min (28cfm)
- 9.5 Litre (2.5 Gal.) polyethylene reservoir
- Stainless Steel carrying frame
- Size (WxLxH) - 420 x 420 x 390 (mm) (16.5" x 16.5" x 15.5")
- Approx weight: 19 Kg (42 lbs)

**HIGH FLOW POWER PACK
HPUTP150002K****Typical use: Subsea and large
tensioner applications**

- 1500 bar (21,750 psi) max working pressure (restricted)
- Calibrated 150mm (6") Pressure gauge
- Flow Rate up to 1.14 litres/min (70 cu.in/min)
- Dual oil outlets with quick-connect no spill couplings
- Pneumatic Filter/Regulator/Lubricator
- Air Consumption 1600 litres/min (56 cfm)
- Stainless Steel carrying frame
- Size (WxLxH) - 465 x 530 x 515 (mm) (18" x 21" x 20")
- Approx weight: 23 Kg (51 lbs)

